Function Index

This index lists functions, symbols, and related terms that are described in this document. References with boldface page numbers are defining references.

A

addr, port object slot, **143**

allocated, port object slot, **143**

B

byte_counter, port object slot, **143**

C

CMAML_allocate_rport, function, **148**

CMAML_allocate_this_rport, function, **148**

CMAML_disable_interrupts, function, **151**

CMAML_enable_interrupts, function, **151**

CMAML_free_rport, function, **148**

CMAML_get_rport_*slot*, function, **148**

CMAML_inside_interrupt_handler, function, **151**

CMAML_interrupt_status, function, **151**

CMAML_number_of_free_rports, function, **148**

CMAML_number_of_rports, function, **148**

CMAML_pcopy, function, **145**

CMAML_poll, function, **153**

CMAML_poll_wait, function, **153**

CMAML_poll_while_lt, function, **153**

CMAML_reply, function, **143**

CMAML_reply_poll, function, **153**

CMAML_reply_tohost, function, **144**

CMAML_request, function, **143**

CMAML_request_poll, function, **153**

CMAML_request_tohost, function, **144**

CMAML_restore_ctrlregs, function, **152**

CMAML_restore_dataregs, function, **152**

CMAML_restore_fpuregs, function, **152**

CMAML_rpc, function, **143**

CMAML_rpc_tohost, function, **144**

CMAML_save_ctrlregs, function, **152**

CMAML_save_dataregs, function, **152**

CMAML_save_fpuregs, function, **152**

CMAML_scopy, function, **145**

CMAML_set_rport_*slot*, function, **148**

CMAML_wait, function, **153**

CMMD_all_channels_free, function, **87**

CMMD_all_channels_free_wait, function, **87**

CMMD_all_msgs_done, function, **68**

Copyright © 1993 Thinking Machines Corporation

CMMD_all_msgs_wait, function, **69**

CMMD_all_receives_done, function, **68**

CMMD_all_sends_done, function, **68**

CMMD_bc_from_host, function, **210**

CMMD_bc_from_host_v, function, **211**

CMMD_bytes_received, function, **46**

CMMD_bytes_sent, function, **46**

CMMD_close_receive_channel, function, **85**

CMMD_close_send_channel, function, **85**

CMMD_concat_elements_to_host, function, **214**

CMMD_concat_with_nodes, function, **111**

CMMD_disable_interrupts, function, **125**

CMMD_distrib_to_nodes, function, **213**

CMMD_enable, function, **206**

CMMD_enable_host, function, **206**

CMMD_enable_interrupts, function, **125**

CMMD_error, function, **186**

CMMD_fget_io_mode, function, **172**

CMMD_free_mcb, function, **67**

CMMD_fset_io_mode, function, **169**

CMMD_gather_from_nodes, function, **214**

CMMD_get_global_or, function, **117**

CMMD_get_io_mode, function, **172**

CMMD_get_open_mode, function, **165**

CMMD_global_creat, function, **167**

CMMD_global_fopen, function, **168**

CMMD_global_open, function, **166**

CMMD_global_socket, function, **175**

CMMD_global_suspend_servers, function, **221**

CMMD_host_node, function, **207**

CMMD_independent, constant, **165**

CMMD_inside_interrupt_handler, function, **125**

CMMD_interrupt_status, function, **125**

CMMD_is_channel_readable, function, **82**

CMMD_is_channel_writable, function, **82**

CMMD_local, constant, **165**

CMMD_mcb_buffer, function, **65**

CMMD_mcb_bytes, function, **65**

CMMD_mcb_dest, function, **65**

CMMD_mcb_node, function, **65**

CMMD_mcb_pending, function, **64**

CMMD_mcb_source, function, **65**

CMMD_mcb_tag, function, **65**

CMMD_msg_done, function, **68**

CMMD_msg_pending, function, **44**

CMMD_msg_sender, function, **46**

CMMD_msg_tag, function, **46**

CMMD_msg_wait, function, **69**

CMMD_node_timer_busy, function, **192**

CMMD_node_timer_clear, function, **189**

CMMD_node_timer_elapsed, function, **192**

CMMD_node_timer_idle, function, **192**

CMMD_node_timer_start, function, **190**

CMMD_node_timer_stop, function, **191**

CMMD_open_receive_channel, function, **77**

CMMD_open_send_channel, function, **77**

CMMD_partition_size, function, **43**

CMMD_physical_blocking_factor, function, **182**

Copyright © 1993 Thinking Machines Corporation

CMMD_physical_read, function, **184**

CMMD_physical_write, function, **183**

CMMD_poll_for_services, function, **221**

CMMD_PR_C_receive, channel state constant, **80**

CMMD_PR_C_send, channel state constant, **80**

CMMD_PR_Close_error, channel state constant, **81**

CMMD_PR_Free, channel state constant, **80**

CMMD_PR_O_receive, channel state constant, **81**

CMMD_PR_O_send, channel state constant, **80**

CMMD_PR_Readable, channel state constant, **81**

CMMD_PR_Sendable, channel state constant, **80**

CMMD_PR_Sent, channel state constant, **80**

CMMD_PR_Unreadable, channel state constant, **81**

CMMD_receive_async, function, **57**

CMMD_receive_bc_from_host, function, **210**

CMMD_receive_bc_from_host_v, function, **211**

CMMD_receive_block, function, **31**

CMMD_receive_block_v, function, **31**

CMMD_receive_channel_status, function, **80**

CMMD_receive_element_from_host, function, **213**

CMMD_reduce_double, function, **97**

CMMD_reduce_float, function, **97**

CMMD_reduce_from_nodes_double, function, **216**

CMMD_reduce_from_nodes_float, function, **216**

CMMD_reduce_from_nodes_int, function, **216**

CMMD_reduce_from_nodes_uint, function, **216**

CMMD_reduce_from_nodes_v, function, **219**

CMMD_reduce_int, function, **97**

CMMD_reduce_to_host_double, function, **216**

CMMD_reduce_to_host_float, function, **216**

CMMD_reduce_to_host_int, function, **216**

CMMD_reduce_to_host_uint, function, **216**

CMMD_reduce_to_host_v, function, **219**

CMMD_reduce_uint, function, **97**

CMMD_reduce_v, function, **99**

CMMD_reset_partition_size, function, **193**

CMMD_reset_receive_channel, function, **84**

CMMD_scan_double, function, **103**

CMMD_scan_float, function, **103**

CMMD_scan_int, function, **102**

CMMD_scan_uint, function, **102**

CMMD_scan_v, function, **108**

CMMD_self_address, function, **42**

CMMD_send_and_receive, function, **34**

CMMD_send_and_receive_v, function, **34**

CMMD_send_async, function, **53**

CMMD_send_block, function, **28**

CMMD_send_block_v, function, **28**

CMMD_send_channel_status, function, **80**

CMMD_send_noblock, function, **60**

CMMD_service_loop, function, **221**

Copyright © 1993 Thinking Machines Corporation

CMMD_set_append_mode, function, **171**

CMMD_set_global_or, function, **117**

CMMD_set_io_mode, function, **169**

CMMD_set_msg_matching_fcn, function, **199**

CMMD_set_open_mode, function, **165**

CMMD_swap, function, **38**

CMMD_swap_v, function, **38**

CMMD_sync_bc, constant, **166**

CMMD_sync_host_with_nodes, function, **208**

CMMD_sync_seq, constant, **166**

CMMD_sync_with_host, function, **208**

CMMD_sync_with_nodes, function, **116**

CMMD_write_channel, function, **83**

D

dftruncate, function, **180**

dlength, function, **177**

dseek, function, **177**

dtell, function, **179**

E

ECMMDBADMODE, I/O error type, **164**

ECMMDINCONSISTENT, I/O error type, **164**

ECMMDNOMATCH, I/O error type, **164**

H

handler, port object slot, **143**

handler_arg2, port object slot, **143**

T

total_nbytes, port object slot, **143**

Copyright © 1993 Thinking Machines Corporation