



NVGRAPH LIBRARY USER'S GUIDE

DU-08010-001_v9.1 | November 2017

TABLE OF CONTENTS

Chapter 1. Introduction.....	1
Chapter 2. nvGRAPH API Reference.....	3
2.1. Return value nvgraphStatus_t.....	3
2.2. nvGRAPH graph topology types.....	4
2.3. nvGRAPH topology structure types.....	4
2.3.1. nvgraphCSCTopology32I_t.....	5
2.3.2. nvgraphCSRTopology32I_t.....	5
2.3.3. nvgraphCOOTopology32I_t.....	6
2.4. Function nvgraphGetProperty().....	6
2.5. Function nvgraphCreate().....	7
2.6. Function nvgraphDestroy().....	7
2.7. Function nvgraphCreateGraphDescr().....	7
2.8. Function nvgraphDestroyGraphDescr().....	8
2.9. Function nvgraphSetGraphStructure().....	8
2.10. Function nvgraphGetGraphStructure().....	9
2.11. Function nvgraphConvertTopology().....	10
2.12. Function nvgraphConvertGraph().....	11
2.13. Function nvgraphAllocateEdgeData().....	12
2.14. Function nvgraphSetEdgeData().....	13
2.15. Function nvgraphGetEdgeData().....	14
2.16. Function nvgraphAllocateVertexData().....	14
2.17. Function nvgraphSetVertexData().....	15
2.18. Function nvgraphGetVertexData().....	16
2.19. Function nvgraphExtractSubgraphByVertex().....	16
2.20. Function nvgraphExtractSubgraphByEdge().....	17
2.21. Function nvgraphWidestPath().....	18
2.22. Function nvgraphSssp().....	19
2.23. Function nvgraphSrSpmv().....	20
2.24. Function nvgraphPagerank().....	21
2.25. Function nvgraphTriangleCount().....	23
2.26. Function nvgraphStatusGetString().....	24
2.27. nvGRAPH Traversal API.....	24
2.27.1. nvGRAPH traversal algorithms.....	24
2.27.2. nvgraphTraversalParameter_t parameter struct.....	24
2.27.3. nvgraphTraversalParameterInit().....	24
2.27.4. nvgraphTraversalSetDistancesIndex().....	25
2.27.5. nvgraphTraversalGetDistancesIndex().....	25
2.27.6. nvgraphTraversalSetPredecessorsIndex().....	26
2.27.7. nvgraphTraversalGetPredecessorsIndex().....	26
2.27.8. nvgraphTraversalSetEdgeMaskIndex().....	27

2.27.9. nvgraphTraversalGetEdgeMaskIndex()	27
2.27.10. nvgraphTraversalSetUndirectedFlag()	27
2.27.11. nvgraphTraversalGetUndirectedFlag()	28
2.27.12. nvgraphTraversalSetAlpha()	28
2.27.13. nvgraphTraversalGetAlpha()	29
2.27.14. nvgraphTraversalSetBeta()	29
2.27.15. nvgraphTraversalGetBeta()	30
2.27.16. nvgraphTraversal()	30
Chapter 3. nvGRAPH Code Examples	32
3.1. nvGRAPH convert topology example	33
3.2. nvGRAPH convert graph example	34
3.3. nvGRAPH pagerank example	35
3.4. nvGRAPH SSSP example	36
3.5. nvGRAPH Semi-Ring SPMV example	37
3.6. nvGRAPH Triangles Counting example	38
3.7. nvGRAPH Traversal example	39

Chapter 1.

INTRODUCTION

Data analytics is a growing application of high-performance computing. Many advanced data analytics problems can be couched as graph problems. In turn, many of the common graph problems today can be couched as sparse linear algebra. This is the motivation for nvGRAPH, new in NVIDIA® CUDA™ 8.0, which harnesses the power of GPUs for linear algebra to handle the largest graph analytics and big data analytics problems.

This release provides graph construction and manipulation primitives, and a set of useful graph algorithms optimized for the GPU. The core functionality is a SPMV (sparse matrix vector product) using a semi-ring model with automatic load balancing for any sparsity pattern. For more information on semi-rings and their uses, we recommend the book "Graph Algorithms in the Language of Linear Algebra", by Jeremy Kepner and John Gilbert.

To use nvGRAPH you should be sure the nvGRAPH library is in the environment (PATH on Windows, LD_LIBRARY_PATH on Linux), "#include nvgraph.h" to your source files referencing the nvGRAPH API, and link your code using -lnvgraph on the command line, or add libnvgraph to your library dependencies. We have tested nvGRAPH using GCC 4.8 and higher on Linux, Visual Studio 2012 and Visual Studio 2014 on Windows.

A typical workflow for using nvGRAPH is to begin by calling nvgraphCreate() to initialize the library. Next the user can proceed to upload graph data to the library through nvGRAPH's API; if there is already a graph loaded in device memory then you just need a pointer to the data arrays for the graph. Graphs may be uploaded using the CSR (compressed sparse row) format and the CSC(compressed column storage) format, using nvgraphCreateGraphDescr(). This creates an opaque handle to the graph object, called the "graph descriptor", which represents the graph topology and its data. Graph data can be attached to vertices and/or edges of the graph, using nvgraphSetVertexData() and nvgraphSetEdgeData() respectively. Multiple values for data can co-exist on each edge or vertex at the same time, each is accessed by an index into the array of data sets. Then the user can execute graph algorithms on the data, extract a subgraph from the data, or reformat the data using the nvGRAPH API. The user can download the results back to host, or copy them to another location on the device, and once all calculations are done the user should call nvgraphDestroy() to free resources used by nvGRAPH.

nvGRAPH depends on features only present in CUDA capability 3.0 and higher architectures. This means that nvGRAPH will only run on Kepler generation or newer cards. This choice was made to provide the best performance possible.

We recommend the user start by inspecting the example codes provided, and adapt from there for their own use.

Chapter 2.

NVGRAPH API REFERENCE

This chapter specifies the behavior of the nvGRAPH library functions by describing their input/output parameters, data types, and error codes.

2.1. Return value `nvgraphStatus_t`

All nvGRAPH Library return values except for `NVGRAPH_STATUS_SUCCESS` indicate that the current API call failed and the user should reconfigure to correct the problem. The possible return values are defined as follows:

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	nvGRAPH operation was successful
<code>NVGRAPH_STATUS_NOT_INITIALIZED</code>	The nvGRAPH library was not initialized. This is usually caused by the lack of a prior call, an error in the CUDA Runtime API called by the nvGRAPH routine, or an error in the hardware setup. To correct: call <code>nvgraphCreate()</code> prior to the function call; and check that the hardware, an appropriate version of the driver, and the nvGRAPH library are correctly installed.
<code>NVGRAPH_STATUS_ALLOC_FAILED</code>	Resource allocation failed inside the nvGRAPH library. This is usually caused by a <code>cudaMalloc()</code> failure.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	An unsupported value or parameter was passed to the function To correct: ensure that all the parameters being passed have valid values.
<code>NVGRAPH_STATUS_ARCH_MISMATCH</code>	The function requires a feature absent from the device architecture. To correct: compile and run the application on a device with appropriate compute capability.
<code>NVGRAPH_STATUS_MAPPING_ERROR</code>	An access to GPU memory space failed.
<code>NVGRAPH_STATUS_EXECUTION_FAILED</code>	The GPU program failed to execute. This is often caused by a launch failure of the kernel on the GPU, which can be caused by multiple reasons.

	To correct: check that the hardware, an appropriate version of the driver, and the nvGRAPH library are correctly installed.
NVGRAPH_STATUS_INTERNAL_ERROR	An internal nvGRAPH operation failed. To correct: check that the hardware, an appropriate version of the driver, and the nvGRAPH library are correctly installed. Also, check that the memory passed as a parameter to the routine is not being deallocated prior to the routine's completion.
NVGRAPH_STATUS_TYPE_NOT_SUPPORTED	The type is not supported by this function. This is usually caused by passing an invalid graph descriptor to the function.
NVGRAPH_STATUS_NOT_CONVERGED	An algorithm failed to converge. To correct: ensure that all the parameters being passed have valid values for this algorithm, increase the maximum number of iteration and/or the tolerance.

2.2. nvGRAPH graph topology types

nvGRAPH separates the topology (connectivity) of a graph from the values. To make specifying a topology easier, nvGRAPH supports three topology types. Each topology type defines its own storage format, which have benefits for some operations but detriments for others. Some algorithms can work only with specific topology types, see the algorithms descriptions for the list of supported topologies.

```
typedef enum
{
    NVGRAPH_CSR_32 = 0,
    NVGRAPH_CSC_32 = 1,
    NVGRAPH_COO_32 = 2
} nvgraphTopologyType_t;
```

Topology types

NVGRAPH_CSR_32	Compressed Sparse Row format (row major format). Used in SrSPMV algorithm. Use <code>nvgraphCSRTopology32I_t</code> topology structure for this format.
NVGRAPH_CSC_32	Compressed Sparse Column format (column major format). Used in SSSP, WidestPath and Pagerank algorithms. Use <code>nvgraphCSCTopology32I_t</code> topology structure for this format.
NVGRAPH_COO_32	Coordinate list format with source or destination major. Not used in any algorithm and provided for data storage only. Use <code>nvgraphCOOTopology32I_t</code> topology structure for this format.

2.3. nvGRAPH topology structure types

Graph topology structures are used to set or retrieve topology data. Users should use the structure that corresponds to the chosen topology type.

2.3.1. nvgraphCSCTopology32I_t

Used for **NVGRAPH_CSC_32** topology type

```
struct nvgraphCSCTopology32I_st {
    int nvertices;
    int nedges;
    int *destination_offsets;
    int *source_indices;
};
typedef struct nvgraphCSCTopology32I_st *nvgraphCSCTopology32I_t;
```

Structure fields

nvertices	Number of vertices in the graph.
nedges	Number of edges in the graph.
destination_offsets	Array of size nvertices +1, where <i>i</i> element equals to the number of the first edge for this vertex in the list of all incoming edges in the source_indices array. Last element stores total number of edges
source_indices	Array of size nedges , where each value designates source vertex for an edge.

2.3.2. nvgraphCSRTopology32I_t

Used for **NVGRAPH_CSR_32** topology type

```
struct nvgraphCSRTopology32I_st {
    int nvertices;
    int nedges;
    int *source_offsets;
    int *destination_indices;
};
typedef struct nvgraphCSRTopology32I_st *nvgraphCSRTopology32I_t;
```

Structure fields

nvertices	Number of vertices in the graph.
nedges	Number of edges in the graph.
source_offsets	Array of size nvertices +1, where <i>i</i> element equals to the number of the first edge for this vertex in the list of all outgoing edges in the destination_indices array. Last element stores total number of edges
destination_indices	Array of size nedges , where each value designates destination vertex for an edge.

2.3.3. nvgraphCOOTopology32I_t

Used for **NVGRAPH_COO_32** topology type

```
struct nvgraphCOOTopology32I_st {
    int nvertices;
    int nedges;
    int *source_indices;
    int *destination_indices;
    nvgraphTag_t tag;
};
typedef struct nvgraphCOOTopology32I_st *nvgraphCOOTopology32I_t;
```

Structure fields

nvertices	Number of vertices in the graph.
nedges	Number of edges in the graph.
source_indices	Array of size nedges , where each value designates the source vertex for an edge.
destination_indices	Array of size nedges , where each value designates the destination vertex for an edge.
tag	One of the values of NVGRAPH_UNSORTED , NVGRAPH_SORT_BY_SOURCE or NVGRAPH_SORT_BY_DESTINATION to indicate topology order.

2.4. Function nvgraphGetProperty()

```
nvgraphStatus_t
nvgraphGetProperty(libraryPropertyType type, int *value);
```

Returns property value of a library, such as version number.

Input

type	Identifier of a library property, such as MAJOR_VERSION , MINOR_VERSION or PATCH_LEVEL
-------------	---

Output

value	Value of a requested property
--------------	-------------------------------

Return Values

NVGRAPH_STATUS_SUCCESS	nvGRAPH successfully created the handle.
NVGRAPH_STATUS_INVALID_VALUE	Invalid property requested.

2.5. Function `nvgraphCreate()`

```
nvgraphStatus_t
    nvgraphCreate(nvgraphHandle_t *handle);
```

Creates only an opaque handle, and allocates small data structures on the host. This handle is used in all of the nvGRAPH functions, so this function should be called first, before any other calls are made to the library.

Input/Output

<code>handle</code>	Pointer to a <code>nvgraphHandle_t</code> object
---------------------	--

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	nvGRAPH successfully created the handle.
<code>NVGRAPH_STATUS_ALLOC_FAILED</code>	The allocation of resources for the handle failed.
<code>NVGRAPH_STATUS_INTERNAL_ERROR</code>	An internal driver error was detected.

2.6. Function `nvgraphDestroy()`

```
nvgraphStatus_t
    nvgraphDestroy(nvgraphHandle_t handle);
```

Destroys a handle created with `nvgraphCreate()`. This will automatically release any allocated memory objects created with this handle, for example any graphs and their vertices' and edges' data. Any subsequent usage of this handle after calling `nvgraphDestroy()` will be invalid. Any calls to the nvGRAPH API after `nvgraphDestroy()` is called will return 'NVGRAPH_UNINITIALIZED' errors.

Input

<code>handle</code>	The <code>nvgraphHandle_t</code> object of the handle to be destroyed.
---------------------	--

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	nvGRAPH successfully destroyed the handle.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	The <code>handle</code> parameter is not a valid handle.

2.7. Function `nvgraphCreateGraphDescr()`

```
nvgraphStatus_t
    nvgraphCreateGraphDescr(nvgraphHandle_t handle, nvgraphGraphDescr_t *descrG);
```

Creates opaque handle for a graph structure. This handle is required for any operation on the graph.

Input

<code>handle</code>	nvGRAPH library handle
---------------------	------------------------

Input/Output

<code>descrG</code>	Pointer to the empty <code>nvgraphGraphDescr_t</code> structure object.
---------------------	---

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	Success
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Bad library handle is provided
<code>NVGRAPH_STATUS_ALLOC_FAILED</code>	Cannot allocate graph descriptor.

2.8. Function `nvgraphDestroyGraphDescr()`

```
nvgraphStatus_t
    nvgraphDestroyGraphDescr(nvgraphHandle_t handle, nvgraphGraphDescr_t descrG);
```

Destroys a graph handle created with `nvgraphCreateGraphDescr()`. This won't release any memory allocated for this graph until the nvGRAPH library handle is destroyed. Calls to manipulate destroyed graphs will return `NVGRAPH_STATUS_INVALID_VALUE`.

Input

<code>handle</code>	nvGRAPH library handle
<code>descrG</code>	Graph descriptor to be released

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	Successful release of the graph descriptor
<code>NVGRAPH_STATUS_TYPE_NOT_SUPPORTED</code>	Graph is stored with unknown type of data
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Invalid library handle or graph descriptor handle

2.9. Function `nvgraphSetGraphStructure()`

```
nvgraphStatus_t
    nvgraphSetGraphStructure( nvgraphHandle_t handle, nvgraphGraphDescr_t descrG,
        void* topologyData, nvgraphTopologyType_t TType);
```

This call sets both topology data and topology type for the given graph descriptor. Graph topology should be set only once. Users should choose one of the supported topologies, fill in the corresponding structure for the graph structure initialization and provide a pointer to this structure. The topology data and type are given in parameters `topologyData` and `TType`. Typically graph topology data includes a number of

vertices, number of edges and connectivity information. Look at the description of the corresponding topology structures for details.

Input

handle	nvGRAPH library handle
topologyData	Pointer to a filled structure of one of the types <code>{nvgraphCSRTopology32I_t, nvgraphCSCTopology32I_t}</code> . The particular type to be used is defined by parameter <code>TType</code> .
TType	Graph topology type. This value should be equal to one of the possible values of the enum <code>nvgraphTopologyType_t</code> . This defines what data structure should be provided by the <code>topologyData</code> parameter.

Input/Output

descrG	Graph descriptor. Must not have topology previously defined.
---------------	--

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	Success
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Invalid library handle, topology data structure pointer or topology values, or graph topology was already set
<code>NVGRAPH_STATUS_TYPE_NOT_SUPPORTED</code>	Provided topology type is not supported
<code>NVGRAPH_STATUS_INTERNAL_ERROR</code>	Unknown internal error was caught

2.10. Function `nvgraphGetGraphStructure()`

```
nvgraphStatus_t
nvgraphGetGraphStructure( nvgraphHandle_t handle, nvgraphGraphDescr_t descrG,
                          void* topologyData, nvgraphTopologyType_t* TType);
```

This function allows users to retrieve a given graph's topology and topology data such as the number of vertices and edges in the graph. Users must provide a graph descriptor as well as an empty topology structure, where this information will be stored.

Input

handle	nvGRAPH library handle
descrG	Graph descriptor. This graph should have its topology structure previously set.

Input/Output

topologyData	Pointer to a structure of one of the types <code>{nvgraphCSRTopology32I_t, nvgraphCSCTopology32I_t}</code> matching the graph topology. If the field is <code>NULL</code> it will be ignored and only graph topology will be returned. The user can point source and destination fields in the structure to a host or device memory to retrieve
---------------------	---

	connectivity information, if one of the fields is NULL it will be ignored.
TType	Pointer to <code>nvgraphTopologyType_t</code> where graph topology will be returned. If the field is NULL it will be ignored and only topology data will be returned.

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	Success
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Invalid library handle, graph descriptor or topology for the graph is not set.
<code>NVGRAPH_STATUS_TYPE_NOT_SUPPORTED</code>	Unsupported topology or graph's topology doesn't match provided parameter.

2.11. Function `nvgraphConvertTopology()`

```
nvgraphStatus_t
    nvgraphConvertTopology(nvgraphHandle_t handle,
                           nvgraphTopologyType_t srcTType, void *srcTopology, void *srcEdgeData,
                           cudaDataType_t *dataType,
                           nvgraphTopologyType_t dstTType, void *dstTopology, void *dstEdgeData);
```

Convert one of the supported topologys to another. In case the source and destination topologies are the same, the function will perform a straight memory copy.

This function assumes that source and destination arrays within the topologies and edge data reside in GPU (device) memory. It is the user's responsibility to allocate memory and copy data between GPU memory and CPU memory using standard CUDA runtime API routines, such as `cudaMalloc()`, `cudaFree()`, `cudaMemcpy()`, and `cudaMemcpyAsync()`.

If the destination topology is `nvgraphCOOTopology32I_st`, the tag field needs to be set to one of the values of `NVGRAPH_UNSORTED`, `NVGRAPH_SORT_BY_SOURCE` or `NVGRAPH_SORT_BY_DESTINATION` to tell the library how the user wants entries sorted (or not).

The function requires extra buffer storage in the device memory for some of the conversion operations, the extra storage is proportional to the topology size. The function is executed asynchronously with respect to the host and may return control to the application on the host before the result is ready.

Input

handle	nvGRAPH library handle.
srcTType	Source topology type. This value should be equal to one of the possible values of the enum <code>nvgraphTopologyType_t</code> . This defines what data structure type should be provided by the <code>srcTopology</code> parameter.
srcTopology	Pointer to a structure of one of the types <code>{nvgraphCSRTopology32I_t, nvgraphCSCTopology32I_t, nvgraphCOOTopology32I_st}</code> . The particular type to

	be used is defined by parameter <code>srcTType</code> . The function assumes that source and destination arrays within the structure reside in device memory.
<code>srcEdgeData</code>	Pointer to the user memoryspace where edge data are stored. Must be device memory.
<code>dataType</code>	Edge data type. This value should be equal to one of <code>CUDA_R_32F</code> or <code>CUDA_R_64F</code> . This defines what data type is provided by the <code>srcEdgeData</code> and <code>dstEdgeData</code> parameters.
<code>dstTType</code>	Destination topology type. This value should be equal to one of the possible values of the enum <code>nvgraphTopologyType_t</code> . This defines what data structure type should be provided by the <code>dstTopology</code> and parameter.

Input/Output

<code>dstTopology</code>	Pointer to a structure of one of the types <code>{nvgraphCSRTopology32I_t, nvgraphCSCTopology32I_t, nvgraphCOOTopology32I_st}</code> where conversion results will be stored. The particular type to be used is defined by parameter <code>dstTType</code> . The function assumes that source and destination arrays within the structure are pre-allocated by the user with at least the number of bytes needed by the topology. Source and destination arrays are assumed to reside in device memory.
<code>dstEdgeData</code>	Pointer to the user memoryspace where converted edge data will be stored. Must be device memory and have at least <code>number_of_vertices*sizeof(dataType)</code> bytes.

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	Success.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Bad parameter(s).
<code>NVGRAPH_STATUS_TYPE_NOT_SUPPORTED</code>	An internal operation failed.
<code>NVGRAPH_STATUS_INTERNAL_ERROR</code>	The type of at least one topology or edge set is not supported. Currently we support float and double type values.

2.12. Function `nvgraphConvertGraph()`

```
nvgraphStatus_t
nvgraphConvertGraph(nvgraphHandle_t handle,
                    nvgraphGraphDescr_t srcDescrG, nvgraphGraphDescr_t dstDescrG,
                    nvgraphTopologyType_t dstTType);
```

Convert one of the supported graph types to another. The function will allocate the necessary memory for the destination graph. It is recommended to use this function over `nvgraphConvertTopology` when converting a large data set.

In addition to the destination graph memory, the function requires extra buffer storage in the device memory for some of the conversion operation, the extra storage is

proportional to the topology size. The function is executed asynchronously with respect to the host and may return control to the application on the host before the result is ready.

Input

<code>handle</code>	nvGRAPH library handle.
<code>srcDescrG</code>	Source graph descriptor. This graph should have its topology structure previously set, and optionally vertex and edge data set.
<code>dstTType</code>	Destination topology type. This value should be equal to one of the possible values of <code>{nvgraphCSRTopology32I_t, nvgraphCSCTopology32I_t, nvgraphCOOTopology32I_t}</code> . This defines what data structure type should be provided by the <code>dstTopology</code> and <code>parameter</code> .

Input/Output

<code>dstDescrG</code>	Destination graph descriptor. Must be an empty descriptor created with <code>nvgraphCreateGraphDescr</code> and not have a topology set.
------------------------	--

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	Success.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Bad parameter(s).
<code>NVGRAPH_STATUS_TYPE_NOT_SUPPORTED</code>	An internal operation failed.
<code>NVGRAPH_STATUS_INTERNAL_ERROR</code>	The type of at least one topology or edge set is not supported. Currently we support float and double type values.

2.13. Function `nvgraphAllocateEdgeData()`

```
nvgraphStatus_t
    nvgraphAllocateEdgeData(nvgraphHandle_t handle, nvgraphGraphDescr_t descrG,
                           size_t numsets, cudaDataType_t *settypes);
```

Allocates one or more storages for the data associated with graph edges. Number of allocated storages is specified by the `numsets` parameter. Types for each of the allocated storages should be provided in the array `settypes` of size `numsets`. Right now nvGRAPH graphs are limited to have data storages to have same type and same size - all elements of `settypes` array should be the same and all of those storages will have number of elements equal to the number of edges in the graph. Vertices data allocated with `nvgraphAllocateVerticesData()` function should have the same datatype as edge data. These storages could later be used in other functions by indices from 0 to `numsets-1`. This function could be called successfully only once for each graph.

Input

<code>handle</code>	nvGRAPH library handle
---------------------	------------------------

numsets	Number of datasets to allocate for the edges. Should be more than 0.
settypes	Array of size numsets that specifies types of allocated datasets. All values in this array should be the same and match graph's datasets data type, if exists.

Input/Output

descrG	Descriptor of the graph for which edge data is allocated. Should not have previously allocated edge data and have its topology properly initialized.
---------------	--

Return Values

NVGRAPH_STATUS_SUCCESS	Success.
NVGRAPH_STATUS_INVALID_VALUE	Invalid function parameters, inconsistent types in the type array, types doesn't match graph's type or graph is not initialized for data allocation.
NVGRAPH_STATUS_TYPE_NOT_SUPPORTED	Types provided in parameter are not supported.

2.14. Function nvgraphSetEdgeData()

```
nvgraphStatus_t
nvgraphSetEdgeData(nvgraphHandle_t handle, nvgraphGraphDescr_t descrG,
void *edgeData, size_t setnum);
```

Update a specific edge value set (weights) of the graph with the user's provided values.

Input

handle	nvGRAPH library handle.
descrG	nvGRAPH graph descriptor, should contain the connectivity information and the edge set setnum
edgeData	Pointer to the data to load into the edge value set. This entry expects to read one value for each edge. Conversions are not supported so the user's type before the void cast should be equivalent to the one specified in nvgraphAllocateEdgeData
setnum	The identifier of the set to update. This assumes that setnum is one of the the edge set allocated in the past using nvgraphAllocateEdgeData . Sets have 0-based index

Return Values

NVGRAPH_STATUS_SUCCESS	Success.
NVGRAPH_STATUS_INVALID_VALUE	Bad parameter(s).
NVGRAPH_STATUS_INTERNAL_ERROR	An internal operation failed.

2.15. Function nvgraphGetEdgeData()

```
nvgraphStatus_t
    nvgraphGetEdgeData(nvgraphHandle_t handle, nvgraphGraphDescr_t descrG,
                      void *edgeData, size_t setnum);
```

Downloads one dataset associated with graph edges using **setnum** index to the user memoryspace. **edgeData** could point to either host or device memoryspace. Size of the data transfer depends on the edges number of the graph and graph's data type.

Input

handle	nvGRAPH library handle.
descrG	Graph descriptor. Graph should contain at least one data set associated with it's vertices
setnum	Index of the source data set of the graph edge data. Value should be between 0 and edge_dataset_number -1

Output

edgeData	Pointer to the user memoryspace where edge data will be stored. Could be either host or device memory and have at least number_of_edges*sizeof(graph_data_type) bytes.
-----------------	---

Return Values

NVGRAPH_STATUS_SUCCESS	Success.
NVGRAPH_STATUS_INVALID_VALUE	Incorrect function parameter, graph has no associated edge data sets or topology type doesn't match.
NVGRAPH_STATUS_TYPE_NOT_SUPPORTED	Graph datatype or topology type is not supported.
NVGRAPH_STATUS_INTERNAL_ERROR	Memory copy failed.

2.16. Function nvgraphAllocateVertexData()

```
nvgraphStatus_t
    nvgraphAllocateVertexData(nvgraphHandle_t handle, nvgraphGraphDescr_t descrG,
                           size_t numsets, cudaDataType_t *settypes);
```

Allocates one or more storages for the data associated with graph vertices. Number of allocated storages is specified by the numsets parameter. Types for each of the allocated storages should be provided in the array settypes of size numsets. Right now nvGRAPH graphs are limited to have data storages to have same type and same size - all elements of settypes array should be the same and all of those storages will have number of elements equal to the number of vertices in the graph. Edge data allocated with nvgraphAllocateEdgeData() function should have the same datatype as vertex data. These storages could later be used in other functions by indices from 0 to **numsets**-1. This function could be called successfully only once for each graph.

Input

handle	nvGRAPH library handle
numsets	Number of datasets to allocate for the vertices. Should be more than 0.
settypes	Array of size numsets that specifies types of allocated datasets. All values in this array should be the same and match graph's datasets data type, if exists.

Input/Output

descrG	Descriptor of the graph for which edge data is allocated. Should not have previously allocated edge data and have its topology properly initialized.
---------------	--

Return Values

NVGRAPH_STATUS_SUCCESS	Success.
NVGRAPH_STATUS_INVALID_VALUE	Invalid function parameters, inconsistent types in the type array, types doesn't match graph's type or graph is not initialized for data allocation.
NVGRAPH_STATUS_TYPE_NOT_SUPPORTED	Types provided in parameter are not supported.

2.17. Function `nvgraphSetVertexData()`

```
nvgraphStatus_t
    nvgraphSetVertexData(nvgraphHandle_t handle, nvgraphGraphDescr_t descrG,
        void *vertexData, size_t setnum);
```

Update a specific vertex value set of the graph with the user's provided values.

Input

handle	nvGRAPH library handle.
descrG	nvGRAPH graph descriptor, should contain the connectivity information and vertex set setnum .
vertexData	Pointer to the data to load into the vertex value set. This entry expects to read one value for each vertex. Conversions are not supported so the user's type before the <code>void</code> cast should be equivalent to the one specified in <code>nvgraphAllocateVertexData</code> .
setnum	The identifier of the set to update. This assumes that setnum is one of the the vertex set allocated in the past using <code>nvgraphAllocateVertexData</code> . Sets have 0-based index

Return Values

NVGRAPH_STATUS_SUCCESS	Success.
NVGRAPH_STATUS_INVALID_VALUE	Bad parameter(s).
NVGRAPH_STATUS_INTERNAL_ERROR	An internal operation failed.

2.18. Function nvgraphGetVertexData()

```
nvgraphStatus_t
    nvgraphGetVertexData(nvgraphHandle_t handle, nvgraphGraphDescr_t descrG,
        void *vertexData, size_t setnum);
```

Downloads one dataset associated with graph vertices using **setnum** index to the user memoryspace. **vertexData** could point to either host or device memoryspace. Size of the data transfer depends on the vertex number of the graph and graph's data type.

Input

handle	nvGRAPH library handle.
descrG	Graph descriptor. Graph should contain at least one data set associated with it's vertices
setnum	Index of the source data set of the graph vertex data. Value should be between 0 and vertex_dataset_number -1

Output

edgeData	Pointer to the user memoryspace where vertex data will be stored. Could be either host or device memory and have at least number_of_vertices*sizeof(graph_data_type) bytes.
-----------------	--

Return Values

NVGRAPH_STATUS_SUCCESS	Success.
NVGRAPH_STATUS_INVALID_VALUE	Incorrect function parameter, graph has no associated vertex data sets or topology type doesn't match.
NVGRAPH_STATUS_TYPE_NOT_SUPPORTED	Graph datatype or topology type is not supported.
NVGRAPH_STATUS_INTERNAL_ERROR	Memory copy failed.

2.19. Function nvgraphExtractSubgraphByVertex()

```
nvgraphStatus_t
    nvgraphExtractSubgraphByVertex(nvgraphHandle_t handle,
        nvgraphGraphDescr_t descrG, nvgraphGraphDescr_t subdescrG,
        int *subvertices, size_t numvertices);
```

Create a new graph by extracting a subgraph given an array of vertices, consisting of row indices in the graph incidence matrix; array must be: (i) free of duplicates; (ii) sorted in ascending order; (iii) must consist of indices with values between 0 and **graph_nvvertices**-1.

Input

handle	nvGRAPH handle of the source graph (original graph)
---------------	---

descrG	nvGRAPH descriptor of the source graph (original graph)
subvertices	array containing vertex indices (row indices in graph incidence matrix) of the subgraph to be extracted; array must be: (i) free of duplicates; (ii) sorted in ascending order; (iii) must consist of indices with values between 0 and graph_nvertices-1 .
numvertices	the size of subvertices[] array. Should be more than 0 and less or equal to the number of graph's vertices.

Output

subdescrG	nvGRAPH graph descriptor of the target graph (subgraph)
------------------	---

Return Values

NVGRAPH_STATUS_SUCCESS	nvGRAPH target (subgraph) was created successfully.
NVGRAPH_STATUS_INVALID_VALUE	Bad parameter(s).
NVGRAPH_STATUS_TYPE_NOT_SUPPORTED	The type of specified nvGRAPH is not supported.

2.20. Function `nvgraphExtractSubgraphByEdge()`

```
nvgraphStatus_t
nvgraphExtractSubgraphByEdge(nvgraphHandle_t handle,
    nvgraphGraphDescr_t descrG, nvgraphGraphDescr_t subdescrG,
    int *subedges, size_t numedges);
```

Create a new graph by extracting a subgraph given an array of edges, consisting of indices in the col_ind[] array of the the graph incidence matrix CSR representation); the array of edges must be: (i) free of duplicates; (ii) sorted in ascending order; (iii) must consist of indices with values between 0 and **graph_nedges-1**.

Input

handle	nvGRAPH handle of the source graph (original graph)
descrG	nvGRAPH descriptor of the source graph (original graph)
subedges	array containing edge indices (indices in the col_ind[] array of the the graph incidence matrix CSR representation) of the subgraph to be extracted; array must be: (i) free of duplicates; (ii) sorted in ascending order; (iii) must consist of indices with values between 0 and graph_nedges-1
numedges	the size of subedges[] array, should be more than 0 and less or equal to number of graph's edges

Output

subdescrG	nvGRAPH graph descriptor of the target graph (subgraph)
------------------	---

Return Values

NVGRAPH_STATUS_SUCCESS	nvGRAPH target (subgraph) was created successfully.
-------------------------------	---

NVGRAPH_STATUS_INVALID_VALUE	Bad parameter(s).
NVGRAPH_STATUS_TYPE_NOT_SUPPORTED	The type of specified nvGRAPH is not supported.

2.21. Function `nvgraphWidestPath()`

```
nvgraphStatus_t
    nvgraphWidestPath(nvgraphHandle_t handle, const nvgraphGraphDescr_t descrG,
                      const size_t weight_index, const int *source_vert,
                      const size_t widest_path_index);
```

Find the widest path from the vertex at source_index to every other vertex; this problem is also known as 'the bottleneck path problem' or 'the maximum capacity path problem'.

If some vertices are unreachable, the widest path to those vertices is $-\infty$. In limited-precision arithmetic, this corresponds to -FLT_MAX or -DBL_MAX depending on the value type of the set (CUDA_R_32F or CUDA_R_64F respectively).

Input

handle	nvGRAPH library handle.
descrG	nvGRAPH graph descriptor, should contain the connectivity information in NVGRAPH_CSC_32 , at least 1 edge set (the capacity) and 1 vertex set (to store the result).
weight_index	Index of the edge set for the weights.
*source_vert	Index of the source, using 0-based indexes.

Output

widest_path_index	The values stored inside the vertex set at widest_path_index (VertexData[widest_path_index]) are the widest path values. VertexData[widest_path_index][i] is the length of the widest path between source_vert and vertex i. If vertex i is not reachable from source_vert, VertexData[widest_path_index][i] = $-\infty$. Users can get a copy of the result using nvgraphGetVertexData
--------------------------	--

Return Values

NVGRAPH_STATUS_SUCCESS	Success.
NVGRAPH_STATUS_INVALID_VALUE	Bad parameter(s).
NVGRAPH_STATUS_TYPE_NOT_SUPPORTED	The type of at least one vertex or edge set is not supported.
NVGRAPH_STATUS_INTERNAL_ERROR	An internal operation failed.

2.22. Function nvgraphSssp()

```
nvgraphStatus_t
nvgraphSssp(nvgraphHandle_t handle, const nvgraphGraphDescr_t descrG,
            const size_t weight_index, const int *source_vert,
            const size_t sssp_index);
```

The Single Source Shortest Path (SSSP) algorithm calculates the shortest path distance from a single vertex in the graph to all other vertices.

If some vertices are unreachable, the shortest path to those vertices is ∞ . In limited-precision arithmetic, that corresponds to FLT_MAX or DBL_MAX depending on the value type of the set (CUDA_R_32F or CUDA_R_64F respectively).

Input

handle	nvGRAPH library handle.
descrG	nvGRAPH graph descriptor, should contain the connectivity information in NVGRAPH_CSC_32, at least 1 edge set (distances) and 1 vertex set (the shortest path lengths).
weight_index	Index of the edge set for the weights. The default value is 0, meaning the first edge set.
*source_vert	Index of the source, using 0-based indexes.

Output

sssp_index	The values stored inside the vertex set at sssp_index (VertexData[sssp_index]) are the shortest path values. VertexData[sssp_index][i] is the length of the shortest path between source_vert and vertex i. If vertex i is not reachable from source_vert, VertexData[sssp_index][i] = ∞ . User can get a copy of the result using <code>nvgraphGetVertexData</code>
-------------------	---

Return Values

NVGRAPH_STATUS_SUCCESS	Success.
NVGRAPH_STATUS_INVALID_VALUE	Bad parameter(s).
NVGRAPH_STATUS_TYPE_NOT_SUPPORTED	The type of at least one vertex or edge set is not supported.
NVGRAPH_STATUS_INTERNAL_ERROR	An internal operation failed.

2.23. Function nvgraphSrpvm()

```
nvgraphStatus_t
nvgraphSrpvm(nvgraphHandle_t handle, const nvgraphGraphDescr_t descrG,
    const size_t weight_index, const void *alpha, const size_t x_index,
    const void *beta, const size_t y_index, const nvgraphSemiring_t SR);
```

The Semi-Ring Sparse Matrix Vector multiplication is an operation of the type $y = \alpha * A * x + \beta y$. Where :

- A is a weighted graph seen as a compressed sparse matrix in CSR, x and y are vectors, α and β are scalars
- $(*,+)$ is a set of two binary operators operating on real values and satisfying semi-ring properties.

In nvGRAPH all semi-rings operate on a set (R) with two binary operators: + and * that satisfies:

- $(R, +)$ is associative, commutative with additive identity (additive_identity + a = a)
- $(R, *)$ is associative with multiplicative identity (multiplicative_identity * a = a)
- Left and Right multiplication is distributive over addition
- Additive identity = multiplicative null operator (null_operator * a = a * null_operator = null_operator).

nvGRAPH's approach for sparse matrix vector multiplication on the GPU is based on the CSRMV merge-path algorithm from Duane Merill. It is designed to handle arbitrary sparsity patterns in an efficient way by offering a good workload balance. As a result, this operation delivers consistent good performance even for networks with a power-law distribution of connections.

nvGRAPH has pre-defined useful semi-ring for graphs in nvgraphSemiring_t, so the user can select them directly.

Semi rings

Semiring	Set	Plus	Times	Add_ident	Mult_ident
NVGRAPH_PLUS_TIMES_SR	R	+	*	0	1
NVGRAPH_MIN_PLUS_SR	$R \cup \{-\infty, +\infty\}$	min	+	∞	0
NVGRAPH_MAX_MIN_SR	$R \cup \{-\infty, +\infty\}$	max	min	$-\infty$	$+\infty$
NVGRAPH_OR_AND_SR	{0.0, 1, 0}	OR	AND	0	1

Input

handle	nvGRAPH library handle.
descrG	nvGRAPH graph descriptor, should contain the connectivity information in NVGRAPH_CSR_32 , at least 1 edge set (weights) and 2 vertex sets (input vector and output vector).
weight_index	Index of the edge set for the weights.
*alpha	Scalar used for multiplication
x_index	Index of the vertex set for used for multiplication
*beta	Scalar used for multiplication. If beta is zero, the vertex set at y_index does not have to be a valid input.
y_index	(optional) Index of the vertex set for used for the addition.
SR	The semi-ring type nvgraphSemiring_t which can be NVGRAPH_PLUS_TIMES_SR , NVGRAPH_MIN_PLUS_SR , NVGRAPH_MAX_MIN_SR , NVGRAPH_OR_AND_SR .

Output

Values at y_index	The values stored inside the set at y_index (VertexData[y_index]) are the result of the operation. User can get a copy of the result using nvgraphGetVertexData
--------------------------	--

Return Values

NVGRAPH_STATUS_SUCCESS	Success.
NVGRAPH_STATUS_INVALID_VALUE	Bad parameter(s).
NVGRAPH_STATUS_TYPE_NOT_SUPPORTED	The type of at least one vertex or edge set is not supported.
NVGRAPH_STATUS_INTERNAL_ERROR	An internal operation failed.

2.24. Function nvgraphPagerank()

```
nvgraphStatus_t
nvgraphPagerank(nvgraphHandle_t handle, const nvgraphGraphDescr_t descrG,
    const size_t weight_index, const void *alpha,
    const size_t bookmark_index,
    const int has_guess, const size_t pagerank_index,
    const float tolerance, const int max_iter);
```

Find the PageRank vertex values for a graph with a given transition matrix (Markov chain), a bookmark vector of dangling vertices, and the damping factor. The transition matrix is sub-stochastic (ie. each row sums to 0 or 1) and has to be provided in column major order (ie. in CSC, which is equivalent to the transposed of the sub-stochastic matrix in CSR). The bookmark vector flags vertices without outgoing edges (also called dangling vertices).

This is equivalent to an eigenvalue problem where we compute the dominant eigenpair. By construction, the maximum eigenvalue is 1, only the eigenvector is interesting. nvGRAPH computes an approximation of the Pagerank eigenvector using the power method. The number of iterations depends on the properties of the network itself; it increases when the tolerance decreases and/or alpha increases toward the limiting value of 1.

The user is free to use default values or to provide inputs for the initial guess, tolerance and maximum number of iterations.

Input

handle	nvGRAPH library handle.
descrG	nvGRAPH graph descriptor, should contain the connectivity information in NVGRAPH_CSC_32 , at least 1 edge set and 2 vertex sets.
weight_index	Index of the edge set for the transition probability.
*alpha	The damping factor alpha represents the probability to follow an outgoing edge, standard value is 0.85. Thus $1.0 - \alpha$ is the probability to “teleport” to a random node. alpha should be greater than 0.0 and strictly lower than 1.0.
bookmark_index	Index of the vertex set for the bookmark of dangling nodes (VertexData[bookmark_index][i] = 1.0 if i is a dangling node, 0.0 otherwise).
has_guess	This parameter is used to notify nvGRAPH if it should use a user-provided initial guess. 0 means the user doesn't have a guess, in this case nvGRAPH will use a uniform vector set to $1/v$. If the value is 1 nvGRAPH will read VertexData[pagerank_index] and use this as initial guess. The initial guess must not be the vector of 0s. Any value other than 1 or 0 is treated as an invalid value.
pagerank_index	(optional) Index of the vertex set for the initial guess if has_guess=1
tolerance	Set the tolerance the approximation, this parameter should be a small magnitude value. The lower the tolerance the better the approximation. If this value is 0.0ϵ , nvGRAPH will use the default value which is $1.0\epsilon-6$. Setting too small a tolerance (less than $1.0E-6$ typically) can lead to non-convergence due to numerical roundoff. Usually 0.01 and 0.0001 are acceptable.
max_iter	The maximum number of iterations before an answer is returned. This can be used to limit the execution time and do an early exit before the solver reaches the convergence tolerance. If this value is lower or equal to 0 nvGRAPH will use the default value, which is 500.

Output

Values at pagerank_index	The values stored inside the vertex set at pagerank_index (VertexData[pagerank_index]) are the PageRank values. VertexData[pagerank_index][i] is the PageRank of vertex i.
---------------------------------	---

	Users can get a copy of the result using <code>nvgraphGetVertexData</code>
--	---

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	The Pagerank iteration reached the desired <code>tolerance</code> in less than <code>max_iter</code> iterations
<code>NVGRAPH_STATUS_NOT_CONVERGED</code>	The Pagerank iteration did not reach the desired <code>tolerance</code> after <code>max_iter</code> iterations
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Bad parameter(s).
<code>NVGRAPH_STATUS_TYPE_NOT_SUPPORTED</code>	The type of at least one vertex or edge set is not supported. Currently we support float and double type values.

2.25. Function `nvgraphTriangleCount()`

```
nvgraphStatus_t
    nvgraphTriangleCount(nvgraphHandle_t handle,
        const nvgraphGraphDescr_t graph_descr,
        uint64_t* result);
```

The triangles counting algorithm calculates number of unique triangles formed by graph edges. Algorithm works on the undirected graphs and graph structure in parameter should store only lower triangular of the adjacency matrix (no diagonal or self loops for vertices).

Input

<code>handle</code>	<code>nvGRAPH</code> library handle.
<code>graph_descr</code>	<code>nvGRAPH</code> graph descriptor, should contain graph connectivity information in <code>NVGRAPH_CSR_32</code> or <code>NVGRAPH_CSC_32</code> format which should contain only lower triangular of adjacency matrix (no diagonal or self loops for vertices).

Output

<code>result</code>	Number of triangles for provided graph will be stored in this parameter.
---------------------	--

Return Values

<code>NVGRAPH_STATUS_SUCCESS</code>	Success.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Bad parameter(s), for example unsupported topology or topology is not stored in the graph.
<code>NVGRAPH_STATUS_MAPPING_ERROR</code>	Incorrect graph handle parameter.
<code>NVGRAPH_STATUS_INTERNAL_ERROR</code>	An internal operation failed.

2.26. Function nvgraphStatusGetString()

```
const char*
nvgraphStatusGetString(nvgraphStatus_t status);
```

Gets string description for the nvGRAPH C API statuses.

Input

status	Status returned from one of the C API functions
---------------	---

Return Values

Pointer to the string with the text description of the C API status.
--

2.27. nvGRAPH Traversal API

This chapter describes nvGRAPH Traversal API types, parameters and functions.

2.27.1. nvGRAPH traversal algorithms

Enum which is used as a parameter to nvgraphTraversal API and which tells nvGRAPH which traversal algorithm to use.

```
typedef enum {
    NVGRAPH_TRAVERSAL_BFS=0
} nvgraphTraversal_t;
```

Algorithms

NVGRAPH_TRAVERSAL_BFS	Use Breadth First Search algorithm for graph traversal.
------------------------------	---

2.27.2. nvgraphTraversalParameter_t parameter struct

```
typedef struct {
    size_t pad[128];
} nvgraphTraversalParameter_t;
```

Array of bytes that is used for passing parameters to various algorithms of nvgraphTraversal API. Should be accessed through the corresponding Get/Set function.

2.27.3. nvgraphTraversalParameterInit()

```
nvgraphStatus_t nvgraphTraversalParameterInit(
    nvgraphTraversalParameter_t *param);
```

This function initializes **traversal parameter** struct with default values.

parameter	Memory	In/out	Meaning
------------------	---------------	---------------	----------------

param	host	output	The pointer to the structure traversal parameters.
--------------	-------------	---------------	--

Status Returned

NVGRAPH_STATUS_SUCCESS	The structure was initialized successfully.
NVGRAPH_STATUS_INVALID_VALUE	Invalid parameter.

2.27.4. nvgraphTraversalSetDistancesIndex()

```
nvgraphStatus_t
nvgraphTraversalSetDistancesIndex(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function sets index of vertex data where distances values will be stored. After successfull traversal this `vertex_data[vertex_id]` will be equal to shortest distance from traversal `source_vertex` to `vertex_id`. Distance to unreachable vertices is $2^{31}-1$ and for source vertex itself - 0.

parameter	Memory	In/out	Meaning
param	host	input/output	The pointer to the structure traversal parameters.
value	host	input	Index of the vertex data where to save distances.

Status Returned

CUSOLVER_STATUS_SUCCESS	Parameter was set successfully in the structure.
NVGRAPH_STATUS_INVALID_VALUE	Invalid parameter.

2.27.5. nvgraphTraversalGetDistancesIndex()

```
nvgraphStatus_t
nvgraphTraversalGetDistancesIndex(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function retrieves index of vertex data for distances from the traversal parameters structure. See `nvgraphTraversalSetDistancesIndex()` description for predecessors data meaning.

parameter	Memory	In/out	Meaning
param	host	input	The pointer to the structure traversal parameters.
value	host	output	Index of the vertex data for distances saved in the param struct.

Status Returned

<code>CUSOLVER_STATUS_SUCCESS</code>	Parameter was retrieved successfully from the params structure.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Invalid parameter.

2.27.6. `nvgraphTraversalSetPredecessorsIndex()`

```
nvgraphStatus_t
nvgraphTraversalSetPredecessorsIndex(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function sets index of vertex data where predecessor of the vertex in shortest path will be stored. After successfull traversal if `vertex_data[vertex_id]=prev_vertex_id` that means that traversal path from `source vertex` to `vertex_id` contains edge from `prev_vertex_id` to `vertex_id`. Predecessor for source vertex and unreachable vertices is -1.

parameter	Memory	In/out	Meaning
<code>param</code>	<code>host</code>	<code>input/output</code>	The pointer to the structure traversal parameters.
<code>value</code>	<code>host</code>	<code>input</code>	Index of the vertex data where predecessors will be stored.

Status Returned

<code>CUSOLVER_STATUS_SUCCESS</code>	Parameter was set successfully in the structure.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Invalid parameter.

2.27.7. `nvgraphTraversalGetPredecessorsIndex()`

```
nvgraphStatus_t
nvgraphTraversalGetPredecessorsIndex(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function retrieves index of vertex data for predecessors from traversal parameters structure. See `nvgraphTraversalSetPredecessorsIndex()` description for predecessors data meaning.

parameter	Memory	In/out	Meaning
<code>param</code>	<code>host</code>	<code>input</code>	The pointer to the structure traversal parameters.
<code>value</code>	<code>host</code>	<code>output</code>	Index of the vertex data for predecessors saved in the param struct.

Status Returned

<code>CUSOLVER_STATUS_SUCCESS</code>	Parameter was retrieved successfully from the params structure.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Invalid parameter.

2.27.8. nvgraphTraversalSetEdgeMaskIndex()

```
nvgraphStatus_t
nvgraphTraversalSetEdgeMaskIndex(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function sets index of edge data where mask for edges will be stored. If for this set of data `edge_data[edge_id]` is 0 then traversal path will not advance using this edge.

parameter	Memory	In/out	Meaning
<code>param</code>	host	input/output	The pointer to the structure traversal parameters.
<code>value</code>	host	input	Index of the edge data where edge mask will be stored.

Status Returned

CUSOLVER_STATUS_SUCCESS	Parameter was set successfully in the structure.
NVGRAPH_STATUS_INVALID_VALUE	Invalid parameter.

2.27.9. nvgraphTraversalGetEdgeMaskIndex()

```
nvgraphStatus_t
nvgraphTraversalGetEdgeMaskIndex(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function retrieves index of an edge data for edge mask from traversal parameters structure. If for this set of data `edge_data[edge_id]` is 0 then traversal path will not advance using this edge.

parameter	Memory	In/out	Meaning
<code>param</code>	host	input	The pointer to the structure traversal parameters.
<code>value</code>	host	output	Index of the edge data for edge mask saved in the param struct.

Status Returned

CUSOLVER_STATUS_SUCCESS	Parameter was retrieved successfully from the params structure.
NVGRAPH_STATUS_INVALID_VALUE	Invalid parameter.

2.27.10. nvgraphTraversalSetUndirectedFlag()

```
nvgraphStatus_t
nvgraphTraversalSetUndirectedFlag(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function sets flag specifying whether processing will be performed on the undirected graph or not.

parameter	Memory	In/out	Meaning
param	host	input/output	The pointer to the structure traversal parameters.
value	host	input	1 if graph is undirected, 0 - otherwise.

Status Returned

CUSOLVER_STATUS_SUCCESS	Parameter was set successfully in the structure.
NVGRAPH_STATUS_INVALID_VALUE	Invalid parameter.

2.27.11. nvgraphTraversalGetUndirectedFlag()

```
nvgraphStatus_t
nvgraphTraversalGetUndirectedFlag(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function retrieves graph direction property flag from traversal parameters structure.

parameter	Memory	In/out	Meaning
param	host	input	The pointer to the structure traversal parameters.
value	host	output	1 if graph is undirected, 0 - otherwise.

Status Returned

CUSOLVER_STATUS_SUCCESS	Parameter was retrieved successfully from the params structure.
NVGRAPH_STATUS_INVALID_VALUE	Invalid parameter.

2.27.12. nvgraphTraversalSetAlpha()

```
nvgraphStatus_t
nvgraphTraversalSetAlpha(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function sets **alpha** parameter for BFS. See <http://parlab.eecs.berkeley.edu/sites/all/parlab/files/main.pdf> paper for the details on meaning of this parameter.

parameter	Memory	In/out	Meaning
param	host	input/output	The pointer to the structure traversal parameters.
value	host	input	Alpha parameter to be set.

Status Returned

<code>CUSOLVER_STATUS_SUCCESS</code>	Parameter was set successfully in the structure.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Invalid parameter.

2.27.13. `nvgraphTraversalGetAlpha()`

```
nvgraphStatus_t
nvgraphTraversalGetAlpha(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function retrieves **alpha** BFS parameter from traversal parameters structure. See <http://parlab.eecs.berkeley.edu/sites/all/parlab/files/main.pdf> paper for the details on meaning of this parameter.

parameter	Memory	In/out	Meaning
<code>param</code>	<code>host</code>	<code>input</code>	The pointer to the structure traversal parameters.
<code>value</code>	<code>host</code>	<code>output</code>	Alpha parameter saved in the traversal parameters structure.

Status Returned

<code>CUSOLVER_STATUS_SUCCESS</code>	Parameter was retrieved successfully from the params structure.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Invalid parameter.

2.27.14. `nvgraphTraversalSetBeta()`

```
nvgraphStatus_t
nvgraphTraversalSetBeta(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function sets **beta** parameter for BFS traversal. See <http://parlab.eecs.berkeley.edu/sites/all/parlab/files/main.pdf> paper for the details on meaning of this parameter.

parameter	Memory	In/out	Meaning
<code>param</code>	<code>host</code>	<code>input/output</code>	The pointer to the structure traversal parameters.
<code>value</code>	<code>host</code>	<code>input</code>	Beta parameter to be set.

Status Returned

<code>CUSOLVER_STATUS_SUCCESS</code>	Parameter was set successfully in the structure.
<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Invalid parameter.

2.27.15. nvgraphTraversalGetBeta()

```
nvgraphStatus_t
nvgraphTraversalGetBeta(
    nvgraphTraversalParameter_t *param,
    const size_t value);
```

This function retrieves **beta** BFS parameter from traversal parameters structure. See <http://parlab.eecs.berkeley.edu/sites/all/parlab/files/main.pdf> paper for the details on meaning of this parameter.

parameter	Memory	In/out	Meaning
param	host	input	The pointer to the structure traversal parameters.
value	host	output	Beta parameter saved in the traversal parameters structure.

Status Returned

CUSOLVER_STATUS_SUCCESS	Parameter was retrieved successfully from the params structure.
NVGRAPH_STATUS_INVALID_VALUE	Invalid parameter.

2.27.16. nvgraphTraversal()

```
nvgraphStatus_t
nvgraphTraversal(nvgraphHandle_t handle,
                const nvgraphGraphDescr_t descrG,
                const nvgraphTraversal_t traversalT,
                const int *source_vert,
                const nvgraphTraversalParameter_t params);
```

This functions performs traversal of the graph specified by **descrG** descriptor from the **source_vert** using traversal **params** with algorithm provided in **traversalT**. See corresponding helper function description to get details on **params** structure meaning for each of the algorithm.

parameter	Memory	In/out	Meaning
descrG	host	input/output	Graph descriptor handle on which traversal will be performed.
traversalT	host	input	Traversal algorithm to be used.
source_vert	host	input	Pointer to the starting vertex for the traversal.
params	host	input	Traversal parameters structure. Use other helper functions to modify parameters values.

Status Returned

CUSOLVER_STATUS_SUCCESS	Traversal was performed successfully.
--------------------------------	---------------------------------------

<code>NVGRAPH_STATUS_INVALID_VALUE</code>	Invalid parameter.
<code>NVGRAPH_STATUS_INTERNAL_ERROR</code>	An internal operation failed.

Chapter 3.

NVGRAPH CODE EXAMPLES

This chapter provides simple examples.

3.1. nvGRAPH convert topology example

```

void check(nvgraphStatus_t status) {
    if (status != NVGRAPH_STATUS_SUCCESS) {
        printf("ERROR : %d\n",status);
        exit(0);
    }
}
int main(int argc, char **argv) {
    size_t n = 6, nnz = 10;
    // nvgraph variables
    nvgraphHandle_t handle;
    nvgraphCSCTopology32I_t CSC_input;
    nvgraphCSRTopology32I_t CSR_output;
    float *src_weights_d, *dst_weights_d;
    cudaDataType_t edge_dimT = CUDA_R_32F;
    // Allocate source data
    CSC_input = (nvgraphCSCTopology32I_t) malloc(sizeof(struct
nvgraphCSCTopology32I_st));
    CSC_input->nvertices = n; CSC_input->nedges = nnz;
    cudaMalloc( (void**)&(CSC_input->destination_offsets), (n+1)*sizeof(int));
    cudaMalloc( (void**)&(CSC_input->source_indices), nnz*sizeof(int));
    cudaMalloc( (void**)&src_weights_d, nnz*sizeof(float));
    // Copy source data
    float src_weights_h[] = {0.333333f, 0.5f, 0.333333f, 0.5f, 0.5f, 1.0f,
0.333333f, 0.5f, 0.5f, 0.5f};
    int destination_offsets_h[] = {0, 1, 3, 4, 6, 8, 10};
    int source_indices_h[] = {2, 0, 2, 0, 4, 5, 2, 3, 3, 4};
    cudaMemcpy(CSC_input->destination_offsets, destination_offsets_h, (n
+1)*sizeof(int), cudaMemcpyDefault);
    cudaMemcpy(CSC_input->source_indices, source_indices_h, nnz*sizeof(int),
cudaMemcpyDefault);
    cudaMemcpy(src_weights_d, src_weights_h, nnz*sizeof(float),
cudaMemcpyDefault);
    // Allocate destination data
    CSR_output = (nvgraphCSRTopology32I_t) malloc(sizeof(struct
nvgraphCSRTopology32I_st));
    cudaMalloc( (void**)&(CSR_output->source_offsets), (n+1)*sizeof(int));
    cudaMalloc( (void**)&(CSR_output->destination_indices), nnz*sizeof(int));
    cudaMalloc( (void**)&dst_weights_d, nnz*sizeof(float));
    // Starting nvgraph and convert
    check(nvgraphCreate (&handle));
    check(nvgraphConvertTopology(handle, NVGRAPH_CSC_32, CSC_input,
src_weights_d,
        &edge_dimT, NVGRAPH_CSR_32, CSR_output, dst_weights_d));
    // Free memory
    check(nvgraphDestroy(handle));
    cudaFree(CSC_input->destination_offsets);
    cudaFree(CSC_input->source_indices);
    cudaFree(CSR_output->source_offsets);
    cudaFree(CSR_output->destination_indices);
    cudaFree(src_weights_d);
    cudaFree(dst_weights_d);
    free(CSC_input);
    free(CSR_output);
    return 0;
}

```

3.2. nvGRAPH convert graph example

```

void check(nvgraphStatus_t status) {
    if (status != NVGRAPH_STATUS_SUCCESS) {
        printf("ERROR : %d\n",status);
        exit(0);
    }
}
int main(int argc, char **argv) {
    size_t n = 6, nnz = 10, vert_sets = 2, edge_sets = 1;
    // nvgraph variables
    nvgraphHandle_t handle; nvgraphGraphDescr_t src_csc_graph;
    nvgraphCSCTopology32I_t CSC_input;
    cudaDataType_t edge_dimT = CUDA_R_32F;
    cudaDataType_t* vertex_dimT;
    // Allocate host data
    float *pr_1 = (float*)malloc(n*sizeof(float));
    void **vertex_dim = (void**)malloc(vert_sets*sizeof(void*));
    vertex_dimT = (cudaDataType_t*)malloc(vert_sets*sizeof(cudaDataType_t));
    CSC_input = (nvgraphCSCTopology32I_t) malloc(sizeof(struct
nvgraphCSCTopology32I_st));
    // Initialize host data
    float weights_h[] = {0.333333f, 0.5f, 0.333333f, 0.5f, 0.5f, 1.0f,
0.333333f, 0.5f, -0.5f, 0.5f};
    int destination_offsets_h[] = {0, 1, 3, 4, 6, 8, 10};
    int source_indices_h[] = {2, 0, 2, 0, 4, 5, 2, 3, 3, 4};
    float bookmark_h[] = {0.0f, 1.0f, 0.0f, 0.0f, 0.0f, 0.0f};
    vertex_dim[0] = (void*)bookmark_h; vertex_dim[1]= (void*)pr_1;
    vertex_dimT[0] = CUDA_R_32F; vertex_dimT[1]= CUDA_R_32F, vertex_dimT[2]=
CUDA_R_32F;
    // Starting nvgraph
    check(nvgraphCreate (&handle));
    check(nvgraphCreateGraphDescr (handle, &src_csc_graph));
    CSC_input->nvertices = n; CSC_input->nedges = nnz;
    CSC_input->destination_offsets = destination_offsets_h;
    CSC_input->source_indices = source_indices_h;
    // Set graph connectivity and properties (transfers)
    check(nvgraphSetGraphStructure(handle, src_csc_graph, (void*)CSC_input,
NVGRAPH_CSC_32));
    check(nvgraphAllocateVertexData(handle, src_csc_graph, vert_sets,
vertex_dimT));
    check(nvgraphAllocateEdgeData (handle, src_csc_graph, edge_sets,
&edge_dimT));
    for (int i = 0; i < 2; ++i)
        check(nvgraphSetVertexData(handle, src_csc_graph, vertex_dim[i], i));
    check(nvgraphSetEdgeData(handle, src_csc_graph, (void*)weights_h, 0));
    // Convert to CSR graph
    nvgraphGraphDescr_t dst_csr_graph;
    check(nvgraphCreateGraphDescr (handle, &dst_csr_graph));
    check(nvgraphConvertGraph(handle, src_csc_graph, dst_csr_graph,
NVGRAPH_CSR_32));
    check(nvgraphDestroyGraphDescr(handle, src_csc_graph));
    check(nvgraphDestroyGraphDescr(handle, dst_csr_graph));
    check(nvgraphDestroy(handle));
    free(pr_1); free(vertex_dim); free(vertex_dimT);
    free(CSC_input);
    return 0;
}

```

3.3. nvGRAPH pagerank example

```

void check(nvgraphStatus_t status) {
    if (status != NVGRAPH_STATUS_SUCCESS) {
        printf("ERROR : %d\n",status);
        exit(0);
    }
}
int main(int argc, char **argv) {
    size_t n = 6, nnz = 10, vert_sets = 2, edge_sets = 1;
    float alpha1 = 0.9f; void *alpha1_p = (void *) &alpha1;
    // nvgraph variables
    nvgraphHandle_t handle; nvgraphGraphDescr_t graph;
    nvgraphCSCTopology32I_t CSC_input;
    cudaDataType_t edge_dimT = CUDA_R_32F;
    cudaDataType_t* vertex_dimT;
    // Allocate host data
    float *pr_1 = (float*)malloc(n*sizeof(float));
    void **vertex_dim = (void**)malloc(vert_sets*sizeof(void*));
    vertex_dimT = (cudaDataType_t*)malloc(vert_sets*sizeof(cudaDataType_t));
    CSC_input = (nvgraphCSCTopology32I_t) malloc(sizeof(struct
nvgraphCSCTopology32I_st));
    // Initialize host data
    float weights_h[] = {0.333333f, 0.5f, 0.333333f, 0.5f, 0.5f, 1.0f,
0.333333f, 0.5f, 0.5f, 0.5f};
    int destination_offsets_h[] = {0, 1, 3, 4, 6, 8, 10};
    int source_indices_h[] = {2, 0, 2, 0, 4, 5, 2, 3, 3, 4};
    float bookmark_h[] = {0.0f, 1.0f, 0.0f, 0.0f, 0.0f, 0.0f};
    vertex_dim[0] = (void*)bookmark_h; vertex_dim[1] = (void*)pr_1;
    vertex_dimT[0] = CUDA_R_32F; vertex_dimT[1] = CUDA_R_32F, vertex_dimT[2] =
CUDA_R_32F;
    // Starting nvgraph
    check(nvgraphCreate (&handle));
    check(nvgraphCreateGraphDescr (handle, &graph));
    CSC_input->nvertices = n; CSC_input->nedges = nnz;
    CSC_input->destination_offsets = destination_offsets_h;
    CSC_input->source_indices = source_indices_h;
    // Set graph connectivity and properties (transfers)
    check(nvgraphSetGraphStructure(handle, graph, (void*)CSC_input,
NVGRAPH_CSC_32));
    check(nvgraphAllocateVertexData(handle, graph, vert_sets, vertex_dimT));
    check(nvgraphAllocateEdgeData (handle, graph, edge_sets, &edge_dimT));
    for (int i = 0; i < 2; ++i)
        check(nvgraphSetVertexData(handle, graph, vertex_dim[i], i));
    check(nvgraphSetEdgeData(handle, graph, (void*)weights_h, 0));

    check(nvgraphPagerank(handle, graph, 0, alpha1_p, 0, 0, 1, 0.0f, 0));
    // Get result
    check(nvgraphGetVertexData(handle, graph, vertex_dim[1], 1));
    check(nvgraphDestroyGraphDescr(handle, graph));
    check(nvgraphDestroy(handle));
    free(pr_1); free(vertex_dim); free(vertex_dimT);
    free(CSC_input);
    return 0;
}

```

3.4. nvGRAPH SSSP example

```

void check(nvgraphStatus_t status) {
    if (status != NVGRAPH_STATUS_SUCCESS) {
        printf("ERROR : %d\n",status);
        exit(0);
    }
}
int main(int argc, char **argv) {
    const size_t n = 6, nnz = 10, vertex_numsets = 1, edge_numsets = 1;
    float *sssp_1_h;
    void** vertex_dim;
    // nvgraph variables
    nvgraphStatus_t status; nvgraphHandle_t handle;
    nvgraphGraphDescr_t graph;
    nvgraphCSCTopology32I_t CSC_input;
    cudaDataType_t edge_dimT = CUDA_R_32F;
    cudaDataType_t* vertex_dimT;
    // Init host data
    sssp_1_h = (float*)malloc(n*sizeof(float));
    vertex_dim = (void**)malloc(vertex_numsets*sizeof(void*));
    vertex_dimT =
    (cudaDataType_t*)malloc(vertex_numsets*sizeof(cudaDataType_t));
    CSC_input = (nvgraphCSCTopology32I_t) malloc(sizeof(struct
    nvgraphCSCTopology32I_st));
    vertex_dim[0] = (void*)sssp_1_h; vertex_dimT[0] = CUDA_R_32F;
    float weights_h[] = {0.333333, 0.5, 0.333333, 0.5, 0.5, 1.0, 0.333333, 0.5,
    0.5, 0.5};
    int destination_offsets_h[] = {0, 1, 3, 4, 6, 8, 10};
    int source_indices_h[] = {2, 0, 2, 0, 4, 5, 2, 3, 3, 4};
    check(nvgraphCreate(&handle));
    check(nvgraphCreateGraphDescr (handle, &graph));
    CSC_input->nvertices = n; CSC_input->nedges = nnz;
    CSC_input->destination_offsets = destination_offsets_h;
    CSC_input->source_indices = source_indices_h;
    // Set graph connectivity and properties (transfers)
    check(nvgraphSetGraphStructure(handle, graph, (void*)CSC_input,
    NVGRAPH_CSC_32));
    check(nvgraphAllocateVertexData(handle, graph, vertex_numsets,
    vertex_dimT));
    check(nvgraphAllocateEdgeData (handle, graph, edge_numsets, &edge_dimT));
    check(nvgraphSetEdgeData(handle, graph, (void*)weights_h, 0));
    // Solve
    int source_vert = 0;
    check(nvgraphSssp(handle, graph, 0, &source_vert, 0));
    // Get and print result
    check(nvgraphGetVertexData(handle, graph, (void*)sssp_1_h, 0));
    //Clean
    free(sssp_1_h); free(vertex_dim);
    free(vertex_dimT); free(CSC_input);
    check(nvgraphDestroyGraphDescr(handle, graph));
    check(nvgraphDestroy(handle));
    return 0;
}

```

3.5. nvGRAPH Semi-Ring SPMV example

```

void check(nvgraphStatus_t status) {
    if (status != NVGRAPH_STATUS_SUCCESS) {
        printf("ERROR : %d\n",status);
        exit(0);
    }
}
int main(int argc, char **argv) {
    size_t n = 5, nnz = 10, vertex_numsets = 2, edge_numsets = 1;
    float alpha = 1.0, beta = 0.0;
    void *alpha_p = (void *)&alpha, *beta_p = (void *)&beta;
    void** vertex_dim;
    cudaDataType_t edge_dimT = CUDA_R_32F;
    cudaDataType_t* vertex_dimT;
    // nvgraph variables
    nvgraphStatus_t status; nvgraphHandle_t handle;
    nvgraphGraphDescr_t graph;
    nvgraphCSRTopology32I_t CSR_input;
    // Init host data
    vertex_dim = (void**)malloc(vertex_numsets*sizeof(void*));
    vertex_dimT =
    (cudaDataType_t*)malloc(vertex_numsets*sizeof(cudaDataType_t));
    CSR_input = (nvgraphCSRTopology32I_t) malloc(sizeof(struct
nvgraphCSRTopology32I_st));
    float x_h[] = {1.1f, 2.2f, 3.3f, 4.4f, 5.5f};
    float y_h[] = {0.0f, 0.0f, 0.0f, 0.0f, 0.0f};
    vertex_dim[0] = (void*)x_h; vertex_dim[1] = (void*)y_h;
    vertex_dimT[0] = CUDA_R_32F; vertex_dimT[1] = CUDA_R_32F;
    float weights_h[] = {1.0f, 4.0f, 2.0f, 3.0f, 5.0f, 7.0f, 8.0f, 9.0f, 6.0f,
1.5f};
    int source_offsets_h[] = {0, 2, 4, 7, 9, 10};
    int destination_indices_h[] = {0, 1, 1, 2, 0, 3, 4, 2, 4, 2};
    check(nvgraphCreate(&handle));
    check(nvgraphCreateGraphDescr(handle, &graph));
    CSR_input->nvertices = n; CSR_input->nedges = nnz;
    CSR_input->source_offsets = source_offsets_h;
    CSR_input->destination_indices = destination_indices_h;
    // Set graph connectivity and properties (transfers)
    check(nvgraphSetGraphStructure(handle, graph, (void*)CSR_input,
NVGRAPH_CSR_32));
    check(nvgraphAllocateVertexData(handle, graph, vertex_numsets,
vertex_dimT));
    for (int i = 0; i < vertex_numsets; ++i)
        check(nvgraphSetVertexData(handle, graph, vertex_dim[i], i));
    check(nvgraphAllocateEdgeData (handle, graph, edge_numsets, &edge_dimT));
    check(nvgraphSetEdgeData(handle, graph, (void*)weights_h, 0));
    // Solve
    check(nvgraphSrpSpMV(handle, graph, 0, alpha_p, 0, beta_p, 1,
NVGRAPH_PLUS_TIMES_SR));
    //Get result
    check(nvgraphGetVertexData(handle, graph, (void*)y_h, 1));
    //Clean
    check(nvgraphDestroyGraphDescr(handle, graph));
    check(nvgraphDestroy(handle));
    free(vertex_dim); free(vertex_dimT); free(CSR_input);
    return 0;
}

```

3.6. nvGRAPH Triangles Counting example

```

#include "stdlib.h"
#include "inttypes.h"
#include "stdio.h"

#include "nvgraph.h"

#define check( a ) \
{\
    nvgraphStatus_t status = (a);\
    if ( (status) != NVGRAPH_STATUS_SUCCESS ) {\
        printf("ERROR : %d in %s : %d\n", status, __FILE__ , __LINE__ );\
        exit(0);\
    }\
}

int main(int argc, char **argv)
{
    // nvgraph variables
    nvgraphHandle_t handle;
    nvgraphGraphDescr_t graph;
    nvgraphCSRTopology32I_t CSR_input;

    // Init host data
    CSR_input = (nvgraphCSRTopology32I_t) malloc(sizeof(struct
nvgraphCSRTopology32I_st));

    // Undirected graph:
    // 0      2-----4
    // \     / \   / \
    //  \   /   \ /   \
    //   1-----3-----5
    // 3 triangles
    // CSR of lower triangular of adjacency matrix:
    const size_t n = 6, nnz = 8;
    int source_offsets[] = {0, 0, 1, 2, 4, 6, 8};
    int destination_indices[] = {0, 1, 1, 2, 2, 3, 3, 4};

    check(nvgraphCreate(&handle));
    check(nvgraphCreateGraphDescr (handle, &graph));
    CSR_input->nvertices = n;
    CSR_input->nedges = nnz;
    CSR_input->source_offsets = source_offsets;
    CSR_input->destination_indices = destination_indices;
    // Set graph connectivity
    check(nvgraphSetGraphStructure(handle, graph, (void*)CSR_input,
NVGRAPH_CSR_32));

    uint64_t trccount = 0;
    check(nvgraphTriangleCount(handle, graph, &trccount));
    printf("Triangles count: %" PRIu64 "\n", trccount);

    free(CSR_input);
    check(nvgraphDestroyGraphDescr(handle, graph));
    check(nvgraphDestroy(handle));
    return 0;
}

```

3.7. nvGRAPH Traversal example

```

void check_status(nvgraphStatus_t status) {
    if ((int)status != 0) {
        printf("ERROR : %d\n",status);
        exit(0);
    }
}
int main(int argc, char **argv){
    //Example of graph (CSR format)
    const size_t n = 7, nnz = 12, vertex_numsets = 2, edge_numset = 0;
    int source_offsets_h[] = {0, 1, 3, 4, 6, 8, 10, 12};
    int destination_indices_h[] = {5, 0, 2, 0, 4, 5, 2, 3, 3, 4, 1, 5};
    //where to store results (distances from source) and where to store results
    (predecessors in search tree)
    int bfs_distances_h[n], bfs_predecessors_h[n];
    // nvgraph variables
    nvgraphStatus_t status;
    nvgraphHandle_t handle;
    nvgraphGraphDescr_t graph;
    nvgraphCSRTopology32I_t CSR_input;
    cudaDataType_t vertex_dimT;
    size_t distances_index = 0;
    size_t predecessors_index = 1;
    vertex_dimT =
    (cudaDataType_t*)malloc(vertex_numsets*sizeof(cudaDataType_t));
    vertex_dimT[distances_index] = CUDA_R_32I;
    vertex_dimT[predecessors_index] = CUDA_R_32I;
    //Creating nvgraph objects
    check_status(nvgraphCreate (&handle));
    check_status(nvgraphCreateGraphDescr (handle, &graph));
    // Set graph connectivity and properties (transfers)
    CSR_input = (nvgraphCSRTopology32I_t) malloc(sizeof(struct
nvgraphCSCTopology32I_st));
    CSR_input->nvertices = n;
    CSR_input->nedges = nnz;
    CSR_input->source_offsets = source_offsets_h;
    CSR_input->destination_indices = destination_indices_h;
    check_status(nvgraphSetGraphStructure(handle, graph, (void*)CSR_input,
NVGRAPH_CSR_32));
    check_status(nvgraphAllocateVertexData(handle, graph, vertex_numsets,
vertex_dimT));
    int source_vert = 1;
    //Setting the traversal parameters
    nvgraphTraversalParameter_t traversal_param;
    nvgraphTraversalParameterInit(&traversal_param);
    nvgraphTraversalSetDistancesIndex(&traversal_param, distances_index);
    nvgraphTraversalSetPredecessorsIndex(&traversal_param, predecessors_index);
    nvgraphTraversalSetUndirectedFlag(&traversal_param, false);
    //Computing traversal using BFS algorithm
    check_status(nvgraphTraversal(handle, graph, NVGRAPH_TRAVERSAL_BFS,
&source_vert, traversal_param));
    // Get result
    check_status(nvgraphGetVertexData(handle, graph, (void*)bfs_distances_h,
distances_index));
    check_status(nvgraphGetVertexData(handle, graph, (void*)bfs_predecessors_h,
predecessors_index));
    // expect bfs distances h = (1 0 1 3 3 2 2147483647)
    for (int i = 0; i<n; i++) printf("Distance to vertex %d: %i\n",i,
bfs_distances_h[i]); printf("\n");
    // expect bfs predecessors = (1 -1 1 5 5 0 -1)
    for (int i = 0; i<n; i++) printf("Predecessor of vertex %d: %i\n",i,
bfs_predecessors_h[i]); printf("\n");
    free(vertex_dimT);
    free(CSR_input);
    check_status(nvgraphDestroyGraphDescr (handle, graph));
    check_status(nvgraphDestroy (handle));
    return 0;
}

```

Notice

ALL NVIDIA DESIGN SPECIFICATIONS, REFERENCE BOARDS, FILES, DRAWINGS, DIAGNOSTICS, LISTS, AND OTHER DOCUMENTS (TOGETHER AND SEPARATELY, "MATERIALS") ARE BEING PROVIDED "AS IS." NVIDIA MAKES NO WARRANTIES, EXPRESSED, IMPLIED, STATUTORY, OR OTHERWISE WITH RESPECT TO THE MATERIALS, AND EXPRESSLY DISCLAIMS ALL IMPLIED WARRANTIES OF NONINFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE.

Information furnished is believed to be accurate and reliable. However, NVIDIA Corporation assumes no responsibility for the consequences of use of such information or for any infringement of patents or other rights of third parties that may result from its use. No license is granted by implication or otherwise under any patent rights of NVIDIA Corporation. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all other information previously supplied. NVIDIA Corporation products are not authorized as critical components in life support devices or systems without express written approval of NVIDIA Corporation.

Trademarks

NVIDIA and the NVIDIA logo are trademarks or registered trademarks of NVIDIA Corporation in the U.S. and other countries. Other company and product names may be trademarks of the respective companies with which they are associated.

Copyright

© 2016-2017 NVIDIA Corporation. All rights reserved.